

Sigma DS4 Financial Card Printer

HIGHLIGHTS

Sigma: The next generation of instant card issuance

Entrust Sigma Financial Card Printers are specifically designed for today's cloud environments and give you the ability to easily issue the most secure financial cards in the world.

- **Simple:** From unboxing to issuing cards to managing your printer, we made sure Sigma was the most user-friendly card issuance solution in the world
- **Secure:** Our industry-leading issuance security architecture will keep your cards and your customers' data safe and secure each step of the issuance process
- **Smart:** Forward-thinking technology and scalability allow you to expand your card issuance program as your needs evolve

KEY FEATURES & BENEFITS

The world's most user-friendly financial card printer

- Intuitive printer dashboard lets you see printer status, order supplies, check cleaning status, update firmware, or contact help – all from your mobile device
- Seamless self-service lets you access how-to videos and other helpful resources by simply scanning a QR code on the LCD display
- Variable LED light ring lets you incorporate brand colors or other customization into your ambient environment
- Pre-loaded ribbon cassettes make switching ribbons easy
- Optional multi-hopper enables multiple card designs from a single printer
- Removable card cassettes make securing cardstock overnight a breeze





Unmatched security

- Dual-control access with security locks protects cardstock, supplies, and rejected cards, meeting Visa and Mastercard security requirements
- Cardstock is easily removable for secure overnight storage
- Secure boot protects system from malware or virus on boot-up
- Trusted Platform Module (TPM) manages the printer's own TLS/SSL certificates and keys
- Connection and data sent between Entrust Adaptive Issuance™ software and printer is encrypted
- Customer data is encrypted and is not stored in the printer after printing is complete
- Secure Ribbon Scramble allows users to specify the card personalization fields that are to be securely printed, making defined personal data difficult to read from the used ribbon supply

Flexible, scalable, and easily integrated into your IT environment

- Issuance capabilities include:
 - Full-color or monochrome direct tocard printing
 - Magnetic stripe encoding
 - Contact or contactless smart card encoding
- Choose on-premises or cloud-hosted deployment
- Easily expand your issuance program as your needs change:
 - Add multi-hopper for multiple pre-designed card feeding
 - Add embosser unit with metallic tipping foil to produce elegant-looking cards
- A full suite of services is available to help ensure your instant issuance program runs smoothly at every one of your branches



TECHNICAL SPECIFICATIONS

Standard Features & Supplies		
Print technology	Dye sublimation / resin thermal transfer	
Print capabilities	Single- or dual-sided edge-to-edge, full-color, and monochrome printing	
Print resolution	 Standard mode: 300 dots per inch (dpi) (300 X 600, 300 X 1200) standard text, bar code, and graphics printing 	
	 Datacard[®] TrueMatch[™] printing technology. Ability to conform to ICC color workflow. 	
Print speed	Single-sided color ribbon (YMCKT): up to 250 cards per hour (cph) Double-sided color ribbon (YMCKT-KT): up to 180 cards per hour (cph) Double-sided monochrome ribbon (black HQ): up to 500 cards per hour (cph	
Card capacity	Input hopper: 125 cards (based on 0.03-in. card thickness) Output hopper: 25 cards Reject holding tray: 10 cards Front exception card slot	
Card sizes	Thickness: 0.010 inches to 0.040 inches (0.25mm - 1.016mm) Dimension: ID-1, CR-79	
Operating environment	Temperature: 60°F to 95°F (15°C to 35°C) Humidity: 20-80% RH – non condensing	
Magnetic stripe encoding	ISO 7811 three-track support (high- and low-coercivity) JIS Type II single-track option	
Smart card encoding	 Single wire connectivity; supports production of EMV level-1 compliant cards Contact smart card encoding: ISO 7816 T=0 (T=1), Class A 5V (3V and 1.8V) Contactless smart card encoding: ISO 14443 - A & B, ISO 15693, MiFare Series, DESFire Series EV1/EV2, HID iCLASS Series, HID Prox (125 KHZ) 	
Security features	 Software-activated lock to secure cardstock, supplies, and reject card hopper TLS/SSL encryption, supports AES-256 Bolt-down ready Secure cable lock (sold separately) Concealed output hopper Password-protected cabinet Non-resettable card counter for auditing 	
Secure Ribbon Scramble	 Printing with Secure Ribbon Scramble allows users to specify the card personalization fields that are to be securely printed, making defined personal data difficult to read from the used ribbon supply Software needed: IFI Software 6.10 or 8.2.6 Available for all UV monochrome ribbons and standard (ISEGA) black and white non-UV ribbons Only recommended for personalization fields; not recommended for non-personalization information 	
LCD display languages	English, Spanish, German, Italian, and Japanese	
Physical dimensions	Printer: L 17.4 in x W 8.9 in x H 9.0 in / 44.2 cm x 22.6 cm x 22.9 cm Printer with optional multi-hopper: 23 in x 13.4 in x 16.2 in (58.4 cm x 34 cm x 41.1 cm)	
Weight	Printer: 12.1 lbs (5.49 kg) Printer with multi-hopper: 30.9 lbs (14.02 kg)	
Connectivity	Ethernet	

Driver operating system support	 Windows 11 Windows 10 version 1909 - 64-bit - enterprise, home, professional Windows 10 - 32 bit - professional or enterprise
Warranties	36 months

Optional Features & Supplies

Multi-hopper	Six-compartmen	Six-compartment hopper, 125-card capacity each (750 cards total)		
Color ribbons	YMCKT	500 images		
	YMCKT-KT	350 images		
	KTT	750 images		
	YMCKL-KT	300 images		
	ST-KT	500 images		
	GT-KT	500 images		
Monochrome ribbons		Black, blue, red, green, silver matte, gold matte, silver metallic, and gold metallic: 1,500 images		

Color ribbon guide: Y=Yellow, M=Magenta, C=Cyan, K=Black, T=Topcoat, S=Silver matte, G=Gold matte



Single-hopper



Multi-hopper

For more information on the Light Curing Module, please refer to the Entrust Sigma DS4 Instant Issuance System with Light Curing Module Data Sheet.



Entrust, Sigma, and the hexagon logo are trademarks, and/or service marks of Entrust Corporation in the U.S. and/or other countries. All other brand or product names are the property of their respective owners. Because we are continuously improving our products and services, Entrust Corporation reserves the right to change specifications without prior notice. Entrust is an equal opportunity employer.

©2023 Entrust Corporation. All rights reserved. DS23Q4-Sigma-DS4-Financial-Card-Printer-DS



Global Headquarters 1187 Park Place, Minneapolis, MN 55379 U.S. Toll-Free Phone: 888 690 2424 International Phone: +1 952 933 1223 info@entrust.com entrust.com/contact